













CAUTION!
ONLY PROFESSIONALS EXPERIENCED AND QUALIFIED IN THE INSTALLATION OF MODULAR VAULTS AND VAULT DOORS SHOULD INSTALL THIS PRODUCT.

NOTES:
1. ALL EXPOSED DOOR & VESTIBULE SURFACES FINISHED IN STAINLESS STEEL.
2. SECURITY BARRIER FOR DOOR AND VESTIBULE ARE CONSTRUCTED OF FIBER REINFORCED CONCRETE.
3. DESIGNED, MANUFACTURED AND TESTED IN ACCORDANCE WITH UL STANDARD UL608 (CERTIFICATION BP6254).
4. STANDARD DAYGATE IS CONSTRUCTED OF CLEAR ANODIZED EXTRUDED ALUMINUM PROFILES AND GRAY ACRYLIC SHEET WITH ADA COMPLIANT LEVER LOCK SET IN US26D FINISH.
5. VESTIBULE IS DESIGNED FOR GROUTLESS INSTALL. IT IS TO BE WELDED TO MODULAR VAULT PANELS 1" WELD EVERY 12" MINIMUM. FULL WELD IS RECOMMENDED.
6. SHIPPING WEIGHT IS 4,000 LBS.
7. VESTIBULE IS CAST WITH TWO LIFT POINTS AT END. REQUEST (P/N 9040-0002) 3/4"T-12 LIFTING SWIVEL AND (P/N 9040-0006) 3/4"x4" COIL BOLT FOR PROPER RIGGING ATTACHMENT.
8. VAULT DOOR REQUIRES INSTALL KIT FOR PROPER INSTALLATION. REQUEST KIT P/N 102-2200.

American Vault® Waco, Texas

DESCRIPTION PRODUCT APPLICATION DRAWING
100 SERIES VAULT DOOR
MODEL 101-01 CL1 LS SHOWN
MODEL 101-02 CL1 RS OPPOSITE

SIZE	DWG. NO.	DATE	SCALE NONE
B	20085	01.07.09	SHEET 1 OF 1